

名称 Name	型号 Grade	规格 St.Size	最高使用温度 Max.Temp	备注 Note	产地 Mfrs.	是否测试? Test or not?	供货周期 Period	最小起订量 Min Order
超高温真空袋 (Ultra High Temperature Vacuum Bagging film)	SI- HTVB-202	0.05/0.075mm×1000mm×Length(可订制)	400°C	★	CN	Y	2w	1RL
	SI- HTVB-203	Thickness: 50/75µm Width: Up to 60"(1520mm) 标准卷长: 150m	400°C		TW	N	4w	5RL
	SI- HTVB-205	50/75µm×1500mm×100m	400°C	★	CN	Y	2w	1RL
超高温隔离膜 (Ultra High Temperature Release film)	SI- HTRF-300	0.0125/0.025/0.05mm×500/1100mm Mother roll:1800m	405°C	Kapton 系列 ★	IRE	Y	10-12w	TBD
超高温玻纤透气毡 (Non-woven Ultra Ultra High Temperature Breather)	SI- HTBR-403	3/6/6.35mm thick, 克重 600-700g/m2 Available in widths Up to 60"(1520mm) 标准卷长: 35m	480°C	★	CN	Y	2w	5RL
超高温可剥布 (Coated Peel Ply)	SI-HTCPP-500	Thick: .006" Width: 38"/50"/60" , 4.0 oz/sq. yard 100 yards per roll	482°C		US	N	12w	10RL
超高温压敏胶带 (Polyimide Ultra High Temperature Pressure Sensitive Tape)	SI-HTPST-600	3.2mm×25/50mm×33m	400°C		CN	Y	2w	40roll/cs
	SI- HTPST-602	1" × 36YDS – 36 rolls/cs 2" × 36YDS – 18 rolls/cs (0.09mm*25/50mm×33m)	400°C	★	US	Y	6w	36/18roll/cs
超高温密封胶条 (Ultra High Temperature Vacuum Bag Sealant Tapes)	SI-HTST-700	3/4" x 1/8" x 30' - 24 rolls/cs	448°C		US	Y	8w	1cs
	SI-HTST -701	1/8" x1/2" x 25' - 40 rolls/case 3/4" x 1/8" x 25' - 32 rolls/case	400°C	★	KR	Y	4w	1cs
	SI-HTST -702	1/8" x1/2" x 25' - 40 rolls/case	400°C		CN	TBD	2w	1cs
超高温真空嘴/管路	SI-HT-VV-800	不锈钢	600°C	★	CN	Y	2w	5 个

超高温真空阀/管 (Ultra High Temperature Vac Valve/Tube)	SI-HT-VT-801	内径 6mm, 不锈钢, 环形柔性接头形式可定制, 长度≥1m	450°C	★	CN	Y	2w	10 根
超高温记号笔 (Ultra High Temperature Marking Pencil)	SI-HTMP-900	颜色: 黑, 红, 蓝, 绿, 紫, 橙, 黄, 茶 书写长度>500m	400°C	★	JP	N	10w	12 支/盒
超高温热电偶 (Ultra High Temperature Thermocouple)	SI-TC-1000	0.76/1.52/2.16/3.18mm×910/1220/1370mm ×30m	450°C	★	US	Y	4w	10 根
超高温喷漆 (Ultra High Temperature Painting)	SI-001	1gallon/桶	460°C		JP	N	10w	4 桶
超高温模具闭孔剂 (Ultra High Temperature Mold Closing Agent)	SI-010	水基 Box of 6 x 0,39 kg Can of 3,9 kg Can of 7,8 kg	460°C		DE	N	8w	1 Box
	SI-011			★	DE	Y	8w	1 Box
	SI-012				DE	N	8w	1 Box
超高温脱模剂 (Ultra High Temperature Mold Closing Agent)	SI-020	水基	450°C	★	DE	Y	8w	1 Box
	SI-021	溶剂基 Box of 6 x 0,39 kg Can of 3,9 kg Can of 7,8 kg	600°C		FR	Y	4w	TBD

★ 为推荐货品, Y 为是, N 为否, TBD 为待确定。